



D4 102

Label Printer

D4 102 is a compact size 4" desktop label printer with a industrial level equipments and high performance. Multiple communication ports, 1 multi function key and LED light to easily operate and show the error status are some of the main features that makes this label printer ideal for labelling application.



ACCESSORIES

TECHNICAL SHEET

	D4 102	D4 102 ETH
Processor	32bit RISC processor	
Programming languages	EPL	
Printing Method	Direct thermal / Thermal transfer	
Resolution	203 dpi	
Print speed	5 ips	
Max. Print Length	3810 mm	
Print Width	104 mm	
Sensors	Moveable reflective sensor (movable from the center to the left side) Cover open sensor Ribbon sensor	
RAM Memory	64 MB SDRAM	
Flash Memory	128 MB	
Control Panel	1 multi-functional keys 6 status LED lights	
Media	Maximum label width: 110 mm Minimum label width: 15 mm Maximum roll diameter: 127 mm Core diameter: 25.4 mm Media thickness: 0.06mm to 0.2mm Media type: Continuous, die-cut, tag, fan-f black mark	
Ribbon	OD: 39 mm Max length: 100 m Width: 25.4 mm to 110 mm ID: 12.7mm Ribbon type: Wax, wax/resin, resin	
Emulation Language	PEPL, PDPL, PZPL	
Interfaces	USB port Ethernet port 10/100 Mbps (option)	USB port Ethernet port 10/100 Mbps on board
Supported 1D/2D Barcodes	Code39 standard or extended, Code39 with check digit, Code93, Code128 UCC, Code128 a modes, Codabar, EAN8, EAN8/13 2&5 digit add-on, EAN13, Interleaved 2 of 5, Interleaved 2 check digit, Interleaved 2 of 5 with human readable check digit, UCC/EAN 128, UPC A, UPC add-on, UPC E, UPC E 2&5 digit add-on, UPC Interleaved 2 of 5, Code11 Data Matrix, MaxiCode, PDF417, QR code	
Fonts	5 internal expandable bitmap fonts (alpha-numeric) Downloadable soft font 4 directions: 0, 90, 180, 270 degrees 2 internal expandable bitmap fonts (numeric only)	
Drivers	Windows® (32/64 bit) – only on request WHQL and silent installation	
Image	PEPL: PCX, Direct binary graphic PDPL : PCX, BMP, HEX	
Options	Peeler kit Guillotine Cutter Ethernet module	
Power	Switching power adapter Input: 100 to 240 V, 1.8 A, 50~60 Hz Output: 24 V, 2.5 A	

D4 102	D4 102 ETH
Environment	Operation: 5 °C to 45°C Storage: -20 °C to 50 °C
Humidity	Operation: 10% to 90% non condensing Storage: 5% to 95% non condensing
Dimensions	263 mm (L) × 200 mm (W) × 188 mm (H)
Weight	2 kg

MODELS



911MK010100233
LABEL PRINTER D4 102 USB
BLACK

911MK010300J33
LABEL PRINTER D4 102 ETH USB
BLACK

Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: 8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice.
Last update: 20 May 2024